

SECTION – 07720 PREFABRICATED TRANSITION-CURB SYSTEM

I. GENERAL

- 1.1 The general conditions and supplemental general conditions of the contract apply to this section as if completely written herein.
- 1.2 The General Contractor shall provide all labor, material and equipment to completely install the Prefabricated Transition-Curb System.

II. PRODUCTS

- 2.1 The Prefabricated Transition-Curb System shall be Model CPT - (specify #1 or 2) as manufactured by: **CURBS PLUS, INC. / 1200 Carline Rd / Rossville, GA 30741**
TOLL FREE 1-888-639-2872

III. CONSTRUCTION

- 3.1 The Prefabricated Transition-Curb System shall be constructed using, minimum 14 gauge LFQ, CQ, G-90 galvanized steel, or heavier gauge (as required). Fully mitered and welded watertight, one-piece construction. Prime painted after fabrication. Load distributing internal reinforcement (as required). Closure angles. Factory insulated with 1” thick neoprene faced fiberglass insulation. Integral supply & return-air transitions.
- 3.2 The Prefabricated Transition-Curb System shall include both base and top gasketing.
- 3.3 Exterior horizontal surfaces shall be sloped to eliminate standing water.

IV. INSTALLATION

- 4.1 The Prefabricated Transition-Curb System must be installed in accordance with instructions and as detailed on drawings.

V. COORDINATION

- 5.1 The Prefabricated Transition-Curb System sizes and options shall be coordinated by Curbs Plus, Inc. and the General and/or Mechanical Contractor prior to fabrication.
- 5.2 Shop drawing approval is required before fabrication.

VI. GUARANTEE

- 6.1 The Prefabricated Transition-Curb System shall be guaranteed to be free from defects in material or workmanship for a period of five years.

END